

# CSB1 P21



- The welded steel frame is heavy duty and durable.
- A removable water tank ensures that the machine can be used even when away from a water source.
- Automatic forward propulsion adds to the ease of use.
- Manual, hydraulic raising and lowering of the blade helps the operator be more precise in the depth of their cut.

## PRODUCT DATA

Item No.	70184645495	Power source	Petrol	Water tank capacity	Optional (25l accessory)
Price (€)	###,##	Motor type	HONDA GX630	Tool speed RPM	1775 min <sup>-1</sup>
		Power	15kW (20 hp)	Starter	Electric
		Blade x bore	Ø 600 x 25,4mm	Raise and lower	Manual hydraulic
		Max. cutting depth	225mm	Propelling	Automatic
		Dimensions (LxWxH)	1200 x 600 x 1100mm	Hand Arm Vibrations	3,35 m/s <sup>2</sup>
		Weight	240kg	Sound power / pressure level	107 dB(A)/89 dB(A)



20 hp



15kW



PETROL

## PRODUCT FEATURES



MAX CUT DEPTH



CONTROL BOX



MANUAL OR HYDRAULIC RAISE & LOWER THE BLADE



REMOVABLE WATER TANK (OPTIONAL)

## DIAMOND BLADE RECOMMENDATIONS FOR CSB1 (PETROL)

Substrate / Material	BETON	BETON	ASPHALT	ASPHALT
Recommended Product	EXTREME BETON	PRO BETON	EXTREME ASPHALT 10	PRO ASPHALT
Diameter	600mm	600mm	600mm	600mm
Bore	25,4mm	25,4mm	25,4mm	25,4mm
Item No.	70184601691	70184611982	70184640192	70184611980
Page reference	27	26	58	59